



1143 NW 52nd Street  
Seattle, WA 98107

**CUSTOMER INFORMATION AND  
TERMS AND CONDITIONS**



(206) 789-9404  
(206) 789-3699 fax

Thank you for choosing American Flamecoat of the Pacific Northwest for you flame retardant application needs. In order to proceed with application and certification, we will need the following information:

**1: CERTIFICATE INFORMATION:**

\_\_\_\_\_  
Name to be listed on the Certificate

**2: BILLING/SHIP TO INFORMATION:**

Bill To: \_\_\_\_\_ Ship To: \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**3. CONTACT INFORMATION**

Phone # \_\_\_\_\_ Cell # \_\_\_\_\_

Email \_\_\_\_\_

**4. MATERIALS TO TREAT:**

Fiber content of fabric or decorative material: (Please list quantity, dimensions, and fiber content. If not known, please indicate, "not known". Please use additional sheets, if needed.

Quantity:	Dimensions:	Fiber Content:	Description:
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

**5. WARRANTY AND DISCLAIMER:**

Deterioration of topical treatments can occur due to atmospheric conditions, cleaning of the surface and many other conditions beyond our control. No additional coatings should be applied to a treated surface as it can change the flame-spread ratings. Fire Retardants shall possess the desired degree of permanency and shall be maintained so as to retain the effectiveness of the treatment under the service conditions encountered in actual use. Periodic testing and inspection should be performed by a trained individual to insure flame-retardancy. Never allow flame retarded fabric to come in contact with any liquids. Dry cleaning of fabric is recommended, but flame-retardant may be removed by washing or dry cleaning.

American Flamecoat will need a small test sample of each fabric treated unless the item is fabricated. Safe-T-Guard is a water soluble fire retardant. During application the fabric will become damp. Some textiles which are water repellent or contain acrylic, nylon, taffeta fibers cannot be made fire retardant. Some textiles use non-colorfast dyes that can bleed, while others may spot, after drying, due to preexisting chemical treatments, existing F/R chemical, or the inherent nature of the textile. The owner of the goods will not hold American Flamecoat liable for changes to a fabrics appearance, feel, or function due to the application of F/R treatments. All orders must be pre-paid via check, Visa, or Master card prior to delivery. After the order is received by American Flamecoat in our office, we will require \_\_\_\_\_ to \_\_\_\_\_ working days to process the order. I am an authorized representative of \_\_\_\_\_ and agree to the above Terms and

Conditions.

\_\_\_\_\_  
Signature Title Date